

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/22/2018

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : MOLDERS CHOICE 87953 LIQUID STEEL POLISH
Product code : 87953

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Molders Choice Inc.
5380 Naiman Parkway
Suite E
Solon, OH 44139
T 440-349-6174

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 4	H227	Combustible liquid
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H227 - Combustible liquid
H315 - Causes skin irritation
H318 - Causes serious eye damage
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P260 - Do not breathe fume, gas, spray, vapors
P264 - Wash hands, forearms and face, clothing thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear eye protection, face shield, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of eye protection, face protection, protective clothing, protective gloves
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor, a POISON CENTER
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use extinguishing powder, foam, carbon dioxide (CO₂) to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to an approved waste disposal plant, an authorized waste collection point

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
solvent naphtha(petroleum), medium aliph.	(CAS No) 64742-88-7	9 - 10	STOT RE 1, H372 Asp. Tox. 1, H304
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	8 - 9	Flam. Liq. 4, H227 Asp. Tox. 1, H304
ammonium hydroxide, 5%≤conc<10%, aqueous solution	(CAS No) 1336-21-6	1 - 3	Skin Corr. 1B, H314 Aquatic Acute 1, H400

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see ... on this label).

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye damage.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.

Storage conditions : Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Emptied containers may retain product residues. Precautions apply to emptied containers. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ammonium hydroxide, 5%<=conc<10%, aqueous solution (1336-21-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm
ACGIH	ACGIH STEL (ppm)	25 ppm
solvent naphtha(petroleum), medium aliph. (64742-88-7)		
Not applicable		
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
Not applicable		

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Creamy white
Odor	: Sweet
Odor threshold	: No data available
pH	: 10 - 11
Melting point	: No Data
Freezing point	: No data available
Boiling point	: 370 - 550 °F @ 760 mmHg
Flash point	: 108 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 1 mm Hg
Relative vapor density at 20 °C	: No data available
Relative density	: 1 @ 68.0 F
Solubility	: Water: < 0.01
Log Pow	: No data available
Auto-ignition temperature	: 420 °F
Decomposition temperature	: No data available
Viscosity	: >= 60 cP
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

solvent naphtha(petroleum), medium aliph. (64742-88-7)

LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 420; Experimental value)
---------------	---

LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
--------------------	--

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
--------------------	---

Skin corrosion/irritation : Causes skin irritation.

pH: 10 - 11

Serious eye damage/irritation : Causes serious eye damage.

pH: 10 - 11

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

solvent naphtha(petroleum), medium aliph. (64742-88-7)

LC50 fish 1	2 - 5 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
-------------	--

EC50 Daphnia 1	1.4 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
----------------	---

Threshold limit algae 1	1 - 3,EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value
-------------------------	---

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LC50 fish 1	> 100 mg/l (Pisces)
-------------	---------------------

EC50 Daphnia 1	> 100 mg/l (Invertebrata)
----------------	---------------------------

Threshold limit algae 1	> 100 mg/l (Algae)
-------------------------	--------------------

12.2. Persistence and degradability

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Persistence and degradability	Not established.
-------------------------------	------------------

ammonium hydroxide, 5%<=conc<10%, aqueous solution (1336-21-6)

Persistence and degradability	Readily biodegradable in water. Ozonation in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air.
-------------------------------	---

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

12.3. Bioaccumulative potential

MOLDERS CHOICE 87953 LIQUID STEEL POLISH	
Bioaccumulative potential	Not established.
ammonium hydroxide, 5%<=conc<10%, aqueous solution (1336-21-6)	
Log Pow	-1.3
Bioaccumulative potential	Bioaccumulation: not applicable.
solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Bioaccumulative potential	No bioaccumulation data available.
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

12.4. Mobility in soil

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Surface tension	0.026 N/m (20 °C)

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to ...
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

TDG

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

MOLDERS CHOICE 87953 LIQUID STEEL POLISH	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	

MOLDERS CHOICE 87953 LIQUID STEEL POLISH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

solvent naphtha(petroleum), medium aliph. (64742-88-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

solvent naphtha(petroleum), medium aliph. (64742-88-7)

Listed on the Canadian DSL (Domestic Substances List)

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product