

Hot Nozzle Gloves

- Made in USA
- Temperature range to 350 & 450° F
- Flexible, Comfortable, Tough, Economical



Inspection Camera – Bore Scope

- 4.3" Screen / 1080 Resolution
- 5.5mm diameter probe
- 6 adjustable LED lights
- Ideal for mold cooling passage inspection
- Waterproof borescope camera to inspect the cooling lines in molds and heat exchangers or other industrial areas



MIN-LUBE™ Grease

- Working Temperature range: -15 °F to 550 °F
- NSF Nonfood Compound Category Code: H1
- Does not contain metals, PTFE or silicone
- Available in sizes 2oz., 16oz., and 5lb containers



Nylon Mold Lifting Slings

- 2 Ply Nylon Web Construction
- 2 Stock Sizes, 1" & 2" wide
- Lengths from 2' to 10' in stock



Forged Quick Adjusting Arching Mold Clamps

- Patented Self Adjusting Height
- Adjustable pivoting washer secured to clamp
- Washer slides in slot to proper clamping position
- 5 sizes to choose from



Duoflow® Aluminum Manifolds

- 3/4", 1", and 1-1/2" inlet sizes (NPT)
- 1/4", 3/8" and 1/2" port sizes (NPT)
- Red & Blue Anodized to identify Supply and Return circuits



Nozzle Leak Detector

- Made in USA
- Includes Alarm Box & plugs to interface to injection machine
- Choice of 4 sizes of sensors: 3, 6, 9 or 12"



Adjustable Ejector Bars

- Made in USA
- Ejector bars are drilled & tapped both ends 1/2-13 thread
- 6 Adjustable Sizes to choose from: 8-10.5", 10-12.5", 12-14.50", 14-16.50", 16-18.50", 21-23.50"



Anti-Seize Compound

- 16 oz. Bottle
- Brush top cap
- Offering Copper, Nickel & Food Grades



Conformal Cooled Sprue Bushings U and B Series

- Reduce cycle time
- Retrofit standard B and U series cold sprue bushings
- Recommended where sprue mass is limiting cycle time

